Q. P. Code: 24754

(3 HOURS)

TOTAL MARKS:80

Note: [1] Q.No.1 is compulsory.

- [2] Attempt any three questions out of remaining five questions
- [3] Assume any data if required and mention clearly.

Q.No.1 Attempt any four:-

[a] Define Irrigation. What is the necessity of irrigation?

[5]

[b] Explain the terms: aquifer, aquiclude and aquifuge.

[5]

[c] Describe various methods of computing average rainfall over a basin.

[5]

[5]

[d] Explain the term 'storage coefficient' and 'coefficient of transmissibility'.

1-1

[e] Explain Canal Lining.

[5]

Q.No.2 [a] What are the factors affecting Run-off. What are various method of computing run-off?

Explain any one method:

[10]

[b] A canal takes off a reservoir to irrigate the areas given below. 40% of the water required for irrigation is assumed to be available directly from precipitation. Channel conveyance losses are 15%. Reservoir losses are 10%. What would be the capacity of reservoir needed? [10]

Crop	Base period (days)	Duty at the field (ha/cumec)	Area under crop (ha			
Wheat	140	1700	400			
Sugarcane	320	800	600			
Rice	120	900	300			
Cotton	220	1200	1200			
Bajra 100		1200	600			

Q.NO.3 [a] Explain various types of Rain-gauge with neat sketches.

[10]

[b] Find the ordinates of a storm hydrograph from a 3hr storm with rainfall of 2, 6.75 and 3.75 cm during subsequent 3 hr intervals. The ordinates of hydrograph are given in the following table:

Hours	3	6	9 .	12	15	18	21	24	3	6	9	12	15	18	21	24
Ordinates of Unit	0	110	365	500	390	310	250	235	175	130	95	65	40	22	10	0
hydrograph	50 4	50	No.		Jan Hell	487			32/0	A		100				
{ cumec}	16 3		100		1			1				100			3. 3.	

Assume an initial loss of 5 mm, infiltration index of 2.5 mm/hr and base flow of 10 cumecs. [10]

Q.No.4 [a] Derive an equation for discharge from a well in an unconfined aquifer. [10] [b] Explain various types of reservoirs. What do you understand by multipurpose [10] reservoir? Q.No.5 [a] A rectangular masonry dam is 3 mt at the base. Compute the maximum permissible height H (a) when no tension is permissible, and (b) when the factor of safety against sliding is 1.5. Given the following: (i) μ =0.5, (ii) density of masonry =24 times the of water, and (iii) c=1. What will be corresponding values of H if uplift is neglected? [10] [10] [b] Discuss the causes of failure of earth dams. [5x4] Write short notes on following: Q.No.6 (a) Hydrologic Cycle and Types of Precipitation (b) Silt extractor and silt ejector (c) Cross Drainage Work (d) Reservoir Planning

Page 2 of 2