QP Code: 31407

				(3 Hours)	[Total Marks :	80
	N. I	(2) (3)	Use Smith chart	e compulsory. e questions from remain wherever necessary. ight indicate full marks		
1.	(a)	What ar		tures. Draw various struc	ctures and give their	5
	(b)	Evnlain	any two modes of	f operation Gunn diodes	with schematics.	5
	(c)	What is	mode jumping in	magnetron. How is it ta	ken care of?	5
	(d)	Explain RADAR	the factors which	h govern the pulse repe	etition frequency in	5
2.	(a) The terminating impedance Σ_L objects. Besign the stage circuited) tuning network to match this load to a 50 Ω line.					10
	(b)	What is	s need of termination f terminations.	ion in microwave system	ns? Explain any two	10
3.	(a)		s Faraday rotation y rotation	in ferrites. Explain work	ing of isolator using	10
	(b)	(b) How does gyrotron tube differ from klystron and magnetron tubes. Explain the principle of operation of gyro TWT amplifier.				
	(.)	T1-i-	the working of a r	parametric amplifier and e	explain its application.	10
4.	(a) (b)	What d	lo you understand	by the term clutter. Explanerate the properties of l	ain the different types	10
5.	(a)	Derive	e an expression for n on range determine	RADAR range. Discuss	effect of radar cross	10
	(h)	Section	n the construction	and working ofTRAPAT	T diode.	10
	(b)) Explai	ii the construction	and working officers		
6.	(a)) Design	a two lumped elem	nent L-section matching Ω to a 50 Ω transmission	network at 1 GHz to line.	10
	(h	transform $Z_L = 10$ -j10 Ω to a 50 Ω transmission line. (b) Write a short note on microwave FET.				
	(0	(c) A radar operating at a wavelength of 0.03m has a maximum range of				
		50 km	n. Its antenna gain	is 2000and the transmit signal is 10pW, then find	tter power is 250 kW.	