QP Code :12515

(3 Hours)

[Total Marks:80

| N. | B.: (1 |) Question no 1 is compulsory. | |
|------|--------|--|----|
| • 1• | (2 | A STATE OF | |
| | (3 | | 20 |
| | | (* (EXAM)* | |
| 1. | Solve | any five :- | |
| | (a) | Compare AM and FM. | |
| | (b) | Derive power relations for A.M. Signals. | |
| | (c) | Write note on RF telemetry. | |
| | (d) | Explain effect of noise in FM modulation. | |
| | (f) | What is modulation? why it is necessary. | |
| | | | |
| 2. | (a) | Explain any one method of F.M. generation with the heip of neat diagram and | 10 |
| | | wave forms. | |
| | (b) | Explain ASK and PAK methods with suitable block diagrams and equations. | 10 |
| | 1 | | |
| 3. | (a) | Explain multiplexing schemes TDM and FDM in detail and compare them. | 10 |
| | (b) | Explain briefly:— | 10 |
| | | (i) Voltage Telemetry | |
| | | (ii) Current Telemetry | |
| | | (iii) Position Telemetry | |
| 4. | (a) | An FM canave is represented by the following:— | 10 |
| | | $V_{FM} = 10 \sin [5 \times 10^8 t + 4 \sin 1250 t]$ | |
| | | find - (i) Carrier and modulating frequencies. | |
| | | (ii) Modulation index and maximum deviation. | |
| | | (iii) Power dissipated by this FM in a 5Ω resistor. | |
| | | (iv) Band width of FM using Carlson rule. | |
| 4. | (b) | Classify and explain various noise sources that affect communication, and derive | 10 |
| | | Friss formula for total noise factor. | |
| _ | | | |
| 5. | (a) | Explain Differential pulse-code modulation (DPCM) in detail. | 10 |
| | (b) | Discuss phase shift method for SSB generation. | 10 |
| , | YY 7 | | 1/ |
| 0. | 100 | short notes on any four :— | 10 |
| | (a) | Preemphasis and deemphasis. | |
| 1 | (b) | Quntisation noise in PCM. | |
| | (c) | Superheterodyne Receivers. Sampling techniques | |
| | | | |

GN-Con.:10584-14.

Delta modulation.