Paper / Subject Code: 39602 / FLUID MECHANICS

S.E. SEM IV / CREDIT BASE / MECH / 27.11.2018

Q. P. Code: 27043

[Marks: 80]

[Time: 3 hours]

Instructions: Question no 1 is COMPULSORY

Attempt any 3 questions from question no 2 to 6 Use illustrative diagrams wherever possible

Assume suitable data if necessary



Q1 Solve any 4 of the 5 sub questions

- Two large plane surfaces are 2.4cm apart. The space between the surfaces is filled with glycerin. What force is required to drag a very thin plate of surface area 0.5 square meter between the two large plane surfaces at a speed of 0.6m/s^2 if the thin plate is at a distance of 0.8cm from one of the plane surfaces? Take dynamic viscosity of glycerin = 0.81 N-s/m^2
- b The stream function for a two dimensional flow is given by $\psi = 2xy$, calculate the velocity of the point P(2,3).
- c A projectile travels in air of pressure 10.1043 N/cm² at 10⁰C at a speed of 1500 5 kmph. Find the Mach number and the Mach angle. Take k=1.4 and R= 287 J/kg K
- **d** Define the following terms :
 - i) Boundary Layer Thickness
 - ii) Displacement Thickness
- e Explain the working of a Orificemeter

5

10

5

- A simple manometer is used to measure the pressure of oil (sp gr 0.8) flowing in the pipeline. It's right limb is open to atmosphere and the left limb is connected to the pipe. The centre of the pipe is 9cm below the level of mercury (sp gr 13.6) in the right limb. If the difference of mercury level in the two limbs is 15cm, determine the absolute pressure of the oil in the pipe in N/cm².
 - A horizontal pipe line 50m long is connected to a water tank at one end discharges freely into the atmosphere at the other end. For the first 30m of its length from the tank, the pipe is 200mm in diameter and its diameter is suddenly enlarged to 400mm. The height of water level in the tank is 10m above the centre of the pipe. Considering all minor losses, determine the rate of flow. Take f = 0.01 for both sections of the pipe.
- Q3 a For a two dimensional potential flow, the velocity potential function is given by: $\Phi = 4x (3y-4)$, determine the velocity at the point (2,3). Also determine the value of the stream function ψ at the point (2,3)
 - b The velocity profile within a laminar boundary layer over a flat plate is given by

$$\frac{u}{U} = 2\left(\frac{y}{\delta}\right) - \left(\frac{y}{\delta}\right)^2$$

Where U is the main stream velocity and δ is the boundary layer thickness. Determine the i) Displacement thickness and ii) Momentum thickness

Paper / Subject Code: 39602 / FLUID MECHANICS

Q. P. Code: 27043

Derive the Euler's equation of motion and obtain the Bernoulli's equation. Q4 the assumptions made. Calculate the stagnation pressure , temperature and density at the stagnation point 10 b on the nose of a plane, which is flying at 800 kmph through still air having a pressure of 8.0 N/cm^2 (abs) and temperature -10 0 C . Take $R=287\ J/kg\ K$ and k=1.4A 300mm diameter pipe carries water under a head of 20 meters with a velocity of 10 Q5 3.5m/s. If the axis of the pipe turns 45°, find the magnitude and the direction of the resultant force of the bend. Assume the pipe to be in the horizontal plane. A fluid of viscosity 0.7 N-s/m² and specific gravity 1.3 is flowing through a circular 10 pipe of diameter 100mm. The maximum shear stress at the pipe wall is given as 192.6 N/m², find the i) pressure gradient ii) average velocity iii) Reynold's number of the flow. Draw a neat sketch of Venturimeter and derive an expression for discharge through 10 Q6 a the venturimeter. Explain the terms Cd, Cv and Cc. Solve any 2 of 3 sub questions below b 5 Define the terms Drag and Lift i 5 State and explain the hydro static law ii 5 Explain the Critical Pressure ratio iii

Page 2 of 2