(03 Hours)

Total Marks: 80

	(05 110415)	00
N.B.:	1. Question No. 1 is compulsory.	
	2. Attempt any three questions out of remaining five questions.	
	3. Assume suitable data wherever required.	1
	4. Assumptions made should be stated clearly.	
Q.1	a) What are the similarities and differences between heat and work.	05
	b) State and explain second law of thermodynamics.	05
	c) What are the basic components of a steam power plant? Enumerate the function of	05
	each component.	
	d) Draw P-v and T-s diagram of dual and Brayton cycle.	05
Q.2		
	expand reversible adiabatically up to 100kPa and then at constant pressure until the	37
	piston regains its original position, heat Is then supplied reversibly with the piston firmly	
	locked in position until the pressure rises to the original value of 20 bar. Calculate the	
	net work done by the gas, for an initial volume of 0.5 m ³ .	10
	b) Air at 1 bar pressure, 290K temperature flows steadily at the rate of 120 hr into a	
	compressor where its pressure and temperature are respectively raised to 15 bar and	
	390K. During the compression process, the heat transfer from the compressor is 10	
	percent of work transfer. Neglecting changes in kinetic energy and potential energy,	
	evaluate the work and heat interactions.	10
Q.3	a) i) State and explain zeroth law of thermodynamics.	1012
	ii) Define path function and point function with example.	10
	b) What is a heat pump? How does it differ from a refrigerator? Show that COP of heat	
	pump is greater than COP of a refrigerator by unity.	10
Q.4	a) i) Write short note on PMM-I and PMM-II.	
	ii) Define availability, dead state and irreversibility.	10
	b) 1m ³ of air is heated reversibly at constant pressure from 290 K to 580 K, and is then	
	cooled reversibly at constant volume back to initial temperature. If the initial pressure is	
	1 bar, work out the net heat flow and overall change in entropy. Represent the processes	10
	on T-S plot.	10
Q.5	SEAL PRODUCTION OF THE SEAL PRODUCTION OF A MAKE CONTROL OF THE SEAL PRODUCTION OF THE SEAL	
	ii) What is cut off ratio? How does it affect the thermal efficiency of Diesel cycle?	10
	b) A steam turbine of a power plant operating on ideal Rankine cycle is supplied with	
	dry saturated steam at 25 bar, and the exhaust takes place at 0.2 bar. For the rate of 10	
	kg/s. Determine i) Quality of steam at the end of expansion ii) Turbine shaft work.	
	iii) Power required to drive the pump iv) work ratio v) Rankine efficiency and vi) heat	
	flow in the condenser.	10
Q.6	a) A vessel of volume 0.04m ³ contains a mixture of saturated water and saturated steam	
	at a temperature of 250°C. The mass of the liquid present is 9 kg. Find the pressure,	
~3	mass, specific volume, enthalpy, entropy and internal energy.	10
	 b) Derive the expression for air standard efficiency of Dual cycle. 	10

AN PO

Course: SE (All Branches)

QP Code 559801

Correction

read 120kg/hr instead of 120m3/hr in QNo.2.b

Date and Time 06/06/2016 04:50 PM