Paper / Subject Code: 88803 / Finite Element Analysis

Sem-II/ CBCGS/Auto/ FEA/MJ2019

Detc: 22 05/19

Max. Marks: 80

Note:

- 1. Question 1 is Compulsory
- 2. Solve any three from remaining five
- 3. Figures to right indicate full marks
- 4. Assume suitable data if necessary
- 0.1 Attempt any four

20

10

10


- a) Explain different types of Boundary conditions giving examples.
- b) Write element matrix equation in the following fields explaining each term:
 - i. 1D steady state, heat transfer by conduction
 - ii. Torsion Analysis
- c) Explain Subparametric, Isoparametric and Superparametric elements.
- d) Explain plane stress and plane strain conditions with examples.
- e) Explain the significance of shape functions.
- a) Solve the following differential equation using Method of least square 0.2 and point Collocation method.

(Assume collocation points x = 0.25 and 0.5)

$$\frac{d^2\Phi}{dx^2} - \Phi = x_3, 0 \le \phi \le 1; \ \phi(0) = 0, \ \phi(1) = 0$$

Compare answer with exact solution at x = 0.5

b) A bar ABC shown in figure is subjected to a load of 60kN at B with a clearance of 1.5mm below the section at C. Area of AB is 150 mm² and length is 1.5m. Area of BC is 240 mm² and length is 3 m. Compute stresses in AB and BC. E=200 GPa.




a) Develop the Finite Element Equation for the most general element using 10 0.3 Rayleigh Ritz method for a vertical bar with axial loading. The governing differential equation is

$$\frac{d}{dx}\left(EA\frac{du}{dx}\right) + f = 0 \qquad ; \quad 0 \le x \le L$$

where f is the weight of the bar per unit length.

10 b) Derive the shape function for a rectangular element in local coordinate system and show its variation over the element.

Q.4 a) Compute the stress developed in the members of the truss shown in figure. E=200 GPa. Area of the member AB is 20 cm² and its length is 5m. Members BC and AC have the same area and is equal to 25 cm².




- b) What do you mean by consistent and lumped mass matrices? Derive the same for linear bar element.
- Q.5 a) Evaluate the natural frequencies for the bar with varying cross sections shown in figure. L = 200 mm, E = 200 GPa and $\rho = 8000 \text{ kg/m}^3$. Consider two elements of equal lengths.



- b) A quadrilateral element is defined by the coordinates (1,4), (4,2), (5,6) and (2,7). The temperatures at the nodes are 20°C, 30°C, 40°C and 25°C respectively. Determine the temperature at a point which has local coordinates $\xi = 0.123$ and $\eta = -0.369$ and also its cartesian coordinates.
- Q.6 a) A triangular plate of size 75mm x 50 mm x 12.5 mm is as shown in figure.

 The modulus of elasticity and Poisson's ratio for plate material are 200 x 10³ N/mm² and 0.25 respectively. Upon loading of the plate, the nodal deflections at node 3 were found to be 0.01552mm and -0.0004 mm in x and y direction respectively. Model the plate with CST element and determine
 - i) The Jacobian for (x,y)-(ξ,η) transformation
 - ii) The strain-displacement relation matrix
 - iii) The stress in plate



b) Explain Convergence criteria. What do you understand by h & p method of Finite Element Analysis?

08

10

12

10