

(3 Hours)

[Total Marks: 80]

## NOTE:

- Question No 1 is **COMPULSORY**.
- Attempt any **THREE** questions from question number **2 to 6**.
- Assume suitable data wherever required.
- Illustrate answers with sketches wherever required.
- Use of steam table is permitted.

20

## 1. Solve the following (any Five)

- Differentiate closed and open cycle gas turbine based on working fluid, efficiency, size of plant and control.
- Differentiate between mounting and accessories with example.
- Differentiate between fire tube and water tube boiler.
- Explain working principle of any one mounting with sketch.
- Define for turbojet engine: Propulsive power and propulsive efficiency.
- State the factors on which nozzle efficiency depends.

6

## 2. (a) Write the difference between Francis and Kaplan turbine.

2

- State impulse momentum principle.

12

- A steam generator evaporates 18000 kg/hr of steam at 12.5 bar and a quality of 0.97 dry from feed water at 105°C, when coal is fired at 2040 kg/hr. If the high calorific value of coal is 27400 kJ/kg. Find: (i) amount of heat supplied in boiler  
(ii) Equivalent evaporation (iii) thermal efficiency.

8

## 3. (a) Explain performance characteristics of water turbines with sketch.

- Following data refers to a stage in a reaction turbine:

Mean blade ring diameter = 1 m, Turbine speed = 3000 rpm, degree of reaction = 50%, exit and inlet angles =  $30^\circ$  &  $50^\circ$ , Steam flow rate = 10000 kg/hr, stage efficiency = 85%. Determine (i) power output of the stage (ii) specific enthalpy drop in kJ/kg (iii) percentage increase in relative velocity of steam over moving blades.

4. (a) Derive an equation for discharge through an isentropic nozzle. 8
- (b) Air enters the compressor of a gas turbine plant operating on air standard cycle at 100 kPa & 300 K with volumetric flow rate 5 m<sup>3</sup>/s. The compressor pressure ratio is 10. The turbine inlet temperature is 1400 K. The turbine and compressor each has an isentropic efficiency of 80%. Calculate (a) thermal efficiency of cycle. (b) 12
- Back work ratio (c) net power developed in kW. (b)
5. (a) An inward flow turbine (reaction type with radial discharge) with an overall efficiency of 80% is required to develop 150 kW. The head is 8 m, peripheral velocity of the wheel is  $0.96\sqrt{2gH}$ . The radial velocity of flow is  $0.36\sqrt{2gH}$ . The wheel is to make 150 rpm. The hydraulic losses in the turbine are 22% of the available energy. Determine: (a) angle of the guide blade at inlet (b) wheel vane angle at inlet (c) diameter of the wheel (d) width of the wheel at inlet. 12
- (b) Define unit speed, unit discharge, unit power & specific speed. Write their equations also. 8
6. (a) Write the detailed classification of jet propulsion engine. 4
- (b) Explain construction and working of Velox boiler. 7
- (c) Why are the steam turbines compounded? Explain. 4
- (d) 2.5 cm diameter jet of water strikes a symmetrical vane tangentially at one end and leaves at the other end. After impingement, the jet gets deflected through 160° by the vane. Calculate the thrust exerted by the jet on the vane if the discharge is 0.0736 m<sup>3</sup>/s. Assume vane to be smooth. 5