Paper / Subject Code: 41972 / Chemical Engineering Equipment Design

	04/06/2025	BE	CHEMICAL	SEM-VII	C-SCHEME	CEED	QP CODE:	100863
--	------------	----	----------	---------	----------	------	----------	--------

Total marks: 80

Time: 3 Hours

(2) (3)	Question No Attempt any Assume suit Figures to th	three quality	estions out if necessar	ry and in					
								ST.	SP
Q1.S	olve any four	question	STA					20	
(8	a) Explain cod	les and sta	ndards for	equipmen	nt design			15	
(1	o) Explain clas	ssification	of heat ex	changers.			25	3	5
(0	e) Explain we	ld joint eff	iciency and	d corrosic	n allowan	ce.	40	5	
(0	d) Explain var	ious ferroi	us and non	ferrous m	aterials of	construction	i		
(6	e) Explain ultı	asonic no	ndestructiv	e testing	method.	STORE OF THE PERSON OF THE PER	25%	AST	
						É	2D,		
Q2. (a)	Write a design	procedur	e with rele	vant equa	tions for e	vaporator.			10
	5				5			ST	
(b)	Explain shrir	nk fit and a	uto-frettag	ge constru	ction of hi	gh pressure	vessel.		10
(A)	Davies a Care	4 4-11	-4 la and annal		dia dia 6	11	ک ^۷ کد		10
Q3. (a)	Design a fixed Shell design				ving the ic	ollowing dat	a		10
	Permissible s	-			mm^2				
	Corrosion all				•				
	Tube design	pressure =	1.5 N/mm	2					
	Tube outside	diameter=	=20mm						
	Tube pitch=	-							
	Tube length=		5						
	Number of tu				_				
	Number of pa	asses on tu	1be side = 2	$\beta = 0.$.7				
	Shell flange: Raised facing	r Gacket 11	sed is flat r	metal iack	rated aches	etos filled			
	Design seating				cica asocs	sios inica			
	Gasket Facto	_		•					
	Allowable str	ess for bo	lt material=	= 138 N/r	nm^2				
	Design shou	ld include							
	i) Shell								
	ii) Shell F	lange							
(b)	Explain diffe	erent types	of support	s used in	process in	dustries.			10

86347 Page 1 of 2

Q4 (a) A tall vertical column 2.5 m in outer diameter and 42 m in height is to be installed. The	3
available specifications are: 10	
Operating temperature and pressure -160° C and 4 kg/cm^2 Skirt height -3.0 m .	
Tray spacing – 0.6 m.	
Top space disengagement – 1.2 m.	
Weir height – 60 mm.	
Bottom space separation – 1.8 m	
Tray loading with liquid – 110 kg/m ²	·
Tray support ring – 45 mm x 45mm x 11 mm angles	
Corrosion allowance – 1.5 mm	
Wind force acting over vent – 110 kg/m ²	
Design pressure $-4 \times 1.2 = 4.8 \text{ kg/cm}^2$	
Insulation thickness – 120 mm.	
Permissible material stress of shell -780 kg/m^2 .	
Welded joint efficiency – 0.80	
Density of shell material. -7600 kg/m^3 .	
Density of insulation -500 kg/m^3 .	
Overhead vapor pressure line – 2280 mm	
Weight of ladder – 30 kg/m.	
Weight of 280 mm outer diameter pipe – 60 kg/m	
(b) Explain different column internals for packed and tray column with neat and labelled	
Adiagram	10
Q 5 (a) List out types of NDT methods. Explain Radiography in detail with neat diagram	10
(b) Which are the different losses while storing the volatile liquids? Explain different	10
types of storage vessels used for storing volatile liquids.	10
types of storage vessels used for storing volatile figures.	
	4.6
Q6. (a)Write a design of agitation system .Design should include	12
i. Design of shaft	
ii. Design of stuffing box and glands	
(b) Explain different types of jackets used for reaction vessels.	08

86347